

MODEL	A		B		C		D		E		F		G/H**	WEIGHT	
	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches		BSP Thread	kg
GT-4	40	1.57	28	1.1	70	2.75	56	2.2	10	0.39	6	0.23	1/8"	0.167	0.37
GT-6	40	1.57	28	1.1	70	2.75	56	2.2	10	0.39	6	0.23	1/8"	0.161	0.35
GT-8	50	1.97	33	1.3	86	3.38	68	2.68	12	0.47	7	0.27	1/8"	0.255	0.55
GT-10	50	1.97	33	1.3	86	3.38	68	2.68	12	0.47	7	0.27	1/8"	0.258	0.57
GT-10-S	50	1.97	33	1.3	86	3.38	68	2.68	12	0.47	7	0.27	1/8"	0.27	0.59
GT13	65	2.56	42	1.65	113	4.45	90	3.54	16	0.63	9	0.35	1/4"	0.555	1.22
GT-16	65	2.56	42	1.65	113	4.45	90	3.54	16	0.63	9	0.35	1/4"	0.566	1.25
GT-16-S	65	2.56	42	1.65	113	4.45	90	3.54	16	0.63	9	0.35	1/4"	0.603	1.33
GT20	80	3.15	56	2.2	128	5.04	104	4.09	16	0.63	9	0.35	1/4"	1.076	2.37
GT-25	80	3.15	56	2.2	128	5.04	104	4.09	16	0.63	9	0.35	1/4"	1.112	2.45
GT-25-S	80	3.15	56	2.2	128	5.04	104	4.09	16	0.63	9	0.35	1/4"	1.193	2.62
GT30	100	3.94	73	2.87	160	6.3	130	5.12	20	0.79	11	0.43	3/8"	2.201	4.84
GT-36	100	3.94	73	2.87	160	6.3	130	5.12	20	0.79	11	0.43	3/8"	2.301	5.06
GT-36-S	100	3.94	73	2.87	160	6.3	130	5.12	20	0.79	11	0.43	3/8"	2.525	5.56
GT40	120	4.72	83	3.26	194	7.63	152	5.98	24	0.94	17	0.66	3/8"	3.696	8.13
GT-48	120	4.72	83	3.26	194	7.63	152	5.98	24	0.94	17	0.66	3/8"	3.858	8.49
GT-48-S	120	4.72	83	3.26	194	7.63	152	5.98	24	0.94	17	0.66	3/8"	4.274	9.4

**Will accept NPT fittings