

MODEL	FREQUENCY V.P.M. X 1000			CENTRIFUGAL FORCE*						AIR CONSUMPTION / MINUTE					
	2 BAR	4 BAR	6 BAR	2 BAR	29 PSI	4 BAR	58 PSI	6 BAR	87 PSI	2 BAR	29 PSI	4 BAR	58 PSI	6 BAR	87 PSI
	29 PSI	58 PSI	87 PSI	N	LBS	N	LBS	N	LBS	LTR.	CF	LTR	CF	LTR.	CF
GT-4	14	14.4	15	135	30	180	40	200	44	33	1.1	58	2	83	2.9
GT-6	11.5	12	12.5	130	29	175	39	210	47	33	1.1	58	2	83	2.9
GT-8	36	42	46	990	222	2060	462	2910	652	46	1.6	80	2.8	112	3.9
GT-10	27.5	35	37.5	840	188	1390	312	2400	538	46	1.6	80	2.8	112	3.9
GT-10-S	17	23	25	650	146	1350	303	1950	437	46	1.6	80	2.8	112	3.9
GT13	26	30	33	1400	313	2440	574	3730	836	120	4.2	200	7	290	10.2
GT-16	17	21.5	24	1220	274	2090	469	3160	708	120	4.2	200	7	290	10.2
GT-16-S	11.5	15.5	17	1100	247	1900	426	2700	605	120	4.2	200	7	290	10.2
GT20	17	20	23	2170	487	4040	906	5520	1238	185	6.6	325	11.4	455	15.9
GT-25	12	15.5	17	2120	475	3510	787	5070	1137	185	6.6	325	11.4	455	15.9
GT-25-S	8.5	11	13	2250	504	3600	807	4900	1098	185	6.6	325	11.4	455	15.9
GT30	13	14	16	3380	578	5430	1217	7540	1690	330	11.5	530	18.5	745	26
GT-36	8	10	13	3290	738	5360	1202	7190	1612	330	11.5	530	18.5	745	26
GT-36-S	6.1	7.2	8.3	4100	919	6200	1390	7500	1681	330	11.5	530	18.5	745	26
GT40	7.7	8.8	9.5	4300	964	7300	1636	9800	2197	425	15	700	24.7	970	34.2
GT-48	6	7.5	9.7	4900	1098	7700	1726	10500	2354	425	15	700	24.7	970	34.2
GT-48-S	-	5.6	6.3	-	-	7500	1681	12000	2691	425	15	700	24.7	970	34.2

*Data obtained on heavy laboratory test block. Frequency and force will decrease on a less rigid mount.



